NH fuse enclosure

# GTT 202

## GTT 202

**NH fuse enclosure**

CUSTOMIZABLE

Productnumber: 02620201
Dimensions: 320 x 320 x 179 mm

NH fuse enclosure, 2 x NH 00 fuse switch disconnector, Shell connection 1.5 - 50 mm², PE/N terminal 2 x 50 mm², assembled on mounting plate, 3 x enclosure connectors (GGV)

**with transparent cover**

IP65 IK08 690V AC 440V DC

# Technical Data

## electrical characteristics

| | |
|---|---|
| Rated operating voltage AC: | 690 V |
| Rated operating voltage DC: | 440 V |
| Rated insulation voltage AC: | 690 V |
| Rated insulation voltage DC: | 1000 V |
| Protection class: | II |
| Type of protection: | IP65 |
| Rated current: | 160 A |
| UL Type Rating: | 3R |

## Dimensions

| | |
|---|---|
| Width: | 320 mm |
| Length: | 320 mm |
| Height: | 179 mm |
| Weight: | 4.372 kg |

## Material characteristics

| | |
|---|---|
| UV-resistant: | yes |
| Halogen free: | yes |
| Flammability class according with UL94: | V2 |
| Glow-wire flammability according to EN 60695-2-11: | 960 °C |

## mechanical properties

| | |
|---|---|
| Impact strength: | IK08 |
| Cover screw torque: | 2.5 Nm |
| Stackable: | yes |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 25°C: | 95 % |
| max. relative humidity 40°C: | 50 % |

## Ambient conditions

| | |
|---|---|
| Min. ambient temperature: | -25 °C |
| Max. ambient temperature: | 40 °C |
| 24h ambient temperature: | 35 °C |
| Installation location: | protected outdoor areas |

## Sales Information

| | |
|---|---|
| EAN: | 4013902051533 |
| Packing Unit Code: | CT |
| ETIM Class: | EC000249 |
| Custom tariff number: | 85369095 |

## Material

| | |
|---|---|
| Base unit material: | Polycarbonate |
| Cover material: | Polycarbonate |
| Sealing material: | Polyurethane |
| Cover screw material: | Polyamide, glass-fibre reinforced |

Created at 12.10.2024. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

## Accessories

07251201 - GFS 12-m - Flange set

07673001 - KPK NH00 - Prism terminal

07675001 - KSR NH 00 - Terminal screws


Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299