

PE/N terminal

PNS 124

PNS 124


PE/N terminal

Productnumber: 07412401

Dimensions: 20 x 340 x 33,5 mm

PE/N terminal for installation in GTA distribution boards as additional terminals or for replacement

2 x 12-pole, 6/16 mm², for GTA 580



Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Rated current:	76 A
Number of poles:	2
shockproof:	No
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	12
Connection 1: Suitable for Cu conductors:	1
Connection 1: Connectable conductor cross-section, single-wire (min):	6 mm ²
Connection 1: Connectable conductor cross-section, single-wire (max):	16 mm ²
Connection 2: Connection type:	Screws
Connection 2: Connectable conductor cross-section, single-wire (min):	1.5 mm ²
Connection 2: Connectable conductor cross-section, single-wire (max):	6 mm ²

Dimensions

Width:	20 mm
Length:	340 mm
Height:	33.5 mm

Material characteristics

Glow-wire flammability according to EN 60695-2-11:	960 °C
Industry quality:	no

mechanical properties

Connection 1: Tightening moment:	1.4 Nm
----------------------------------	--------

Material

Insulating body material:	Thermoplastic
---------------------------	---------------