

Busbar terminal

## SKL 116

### SKL 116

**Busbar terminal**

Productnumber: 07511601

Dimensions: 12 x 25,5 x 31,5 mm

Busbar terminal, for copper rails 12/20/25/30 x 10 mm

**for CU conductor 1x (1.5-16mm<sup>2</sup>) re/rm/rf+AE**



16<sup>2</sup>

## Technical Data

### electrical characteristics

Max. conductor cross section:	16 mm <sup>2</sup>
Rated current:	180 A
Number of poles:	1
shockproof:	No
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	1
Connection 1: Suitable for Cu conductors:	1
Connection 1: Suitable for Al conductors:	0
Connection 1: Connectable conductor cross-section, single-wire (min):	1.5 mm <sup>2</sup>
Connection 1: Connectable conductor cross-section, single-wire (max):	16 mm <sup>2</sup>
Connection 1: Connectable conductor cross-section, stranded (min):	1.5 mm <sup>2</sup>
Connection 1: Connectable conductor cross-section, stranded (max):	16 mm <sup>2</sup>

### Dimensions

Width:	12 mm
Length:	25.5 mm
Height:	31.5 mm

### Material characteristics

Industry quality:	no
-------------------	----

### mechanical properties

Connection 1: Tightening moment:	3 Nm
----------------------------------	------