

Busbar terminal

SKL 135



SKL 135

Busbar terminal

Productnumber: 07513501

Dimensions: 16 x 26,5 x 36 mm

Busbar terminal, for copper rails 12/20/25/30 x 10 mm

for CU conductor 1x (4-35mm²) re/rm/sm/rf+AE, lam. Flat copper 3x9x0.8mm, 6x9x0.8mm

35²

Technical Data

electrical characteristics

| | |
|---|--------------------|
| Max. conductor cross section: | 35 mm ² |
| Rated current: | 270 A |
| Number of poles: | 1 |
| shockproof: | No |
| Connection 1: Connection type: | Screws |
| Connection 1: Clamping points per pole: | 1 |
| Connection 1: Suitable for Cu conductors: | 1 |
| Connection 1: Suitable for Al conductors: | 0 |
| Connection 1: Connectable conductor cross-section, single-wire (min): | 4 mm ² |
| Connection 1: Connectable conductor cross-section, single-wire (max): | 35 mm ² |
| Connection 1: Connectable conductor cross-section, stranded (min): | 4 mm ² |
| Connection 1: Connectable conductor cross-section, stranded (max): | 35 mm ² |

Dimensions

| | |
|---------|---------|
| Width: | 16 mm |
| Length: | 26.5 mm |
| Height: | 36 mm |

Material characteristics

| | |
|-------------------|----|
| Industry quality: | no |
|-------------------|----|

mechanical properties

| | |
|----------------------------------|------|
| Connection 1: Tightening moment: | 6 Nm |
|----------------------------------|------|