

Terminal block enclosure

## ALR 2320-4<sup>2</sup>



### ALR 2320-4<sup>2</sup>

Terminal block enclosure

CUSTOMIZABLE

Productnumber: 16041401

Dimensions: 230 x 200 x 111 mm

Terminal block enclosure, protection class IP66, nominal cross-section 4 mm<sup>2</sup>, Ui=400V AC, Aluminium, powder-coated painting, internal fixing points, for installations in industrial environments and protected outdoor areas

**equipped with 26-pole terminal block 4mm<sup>2</sup>  
(Contaclip RK 2.5-4 type)**



## Technical Data

### electrical characteristics

Rated insulation voltage AC:	400 V
Max. conductor cross section:	4 mm <sup>2</sup>
Type of protection:	IP66
UL Type Rating:	not specified

### Dimensions

Width:	230 mm
Length:	200 mm
Height:	111 mm

### Material characteristics

UV-resistant:	yes
Halogen free:	yes
Industry quality:	yes

### mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK09
Sealable:	yes
Fastening:	internal fixing points

### Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	75 °C
24h ambient temperature:	60 °C
Installation location:	protected outdoor areas

## Material

Base unit material:	Aluminium, powder-coated painting
---------------------	-----------------------------------

## Accessories

[15400601 - AL ALS-gro - External attachment set](#)

[15421001 - AL ASS - External hinge set](#)