

Double-membrane seals

DMS M20/w



DMS M20/w

Double-membrane seals

Productnumber: 26012001

Dimensions: 25,2 x 25,2 x 13,4 mm

Double membrane seals, IP66, with two sealing membranes, closed, thermoplastic elastomer (TPE), for wall thicknesses 1.5 - 4.5 mm, white

Sealing range 7 - 13 mm



Technical Data

electrical characteristics

| | |
|---------------------|------|
| Type of protection: | IP66 |
|---------------------|------|

Colours

| | |
|-------------------|-------------|
| Accessory colour: | clear white |
|-------------------|-------------|

Dimensions

| | |
|--------|---------|
| Width: | 25.2 mm |
|--------|---------|

| | |
|---------|---------|
| Length: | 25.2 mm |
|---------|---------|

| | |
|---------|---------|
| Height: | 13.4 mm |
|---------|---------|

| | |
|---------------|-----|
| Nominal size: | M20 |
|---------------|-----|

Material characteristics

| | |
|---------------|-----|
| UV-resistant: | yes |
|---------------|-----|

| | |
|---------------|-----|
| Halogen free: | yes |
|---------------|-----|

| | |
|-------------------|----|
| Industry quality: | no |
|-------------------|----|

mechanical properties

| | |
|-------------------------|--------|
| for wall thickness max: | 4.5 mm |
|-------------------------|--------|

| | |
|------------------------|------|
| for sealing range min: | 7 mm |
|------------------------|------|

| | |
|------------------------|-------|
| for sealing range max: | 13 mm |
|------------------------|-------|

| | |
|-------------------------|--------|
| for wall thickness min: | 1.5 mm |
|-------------------------|--------|

Ambient conditions

| | |
|------------------------|-------------------------|
| Installation location: | protected outdoor areas |
|------------------------|-------------------------|

Material

| | |
|---------------------|--------|
| Accessory material: | Rubber |
|---------------------|--------|
