


Channel installation box

## **KD 2 70/55 K1 sw**



### **KD 2 70/55 K1 sw**

#### **Channel installation box**

Productnumber: 39205501

Dimensions: 55 mm

Channel installation box, rated insulation voltage:  
400V AC, certified by VDE (DIN EN 50085-1 (VDE  
0604-1))

**2-way, for installation in Tehalit and  
Ackermannwall trunkings/device installation  
ducts**



---

## Technical Data

### electrical characteristics

---

Rated insulation voltage AC:	400 V
------------------------------	-------

---

### Colours

---

Cover colour:	green
---------------	-------

---

### Dimensions

---

Height:	55 mm
---------	-------

---

### Material characteristics

---

Halogen free:	no
---------------	----

---

Industry quality:	no
-------------------	----

---

### Ambient conditions

---

max. relative humidity 25°C:	100 %
------------------------------	-------

---

max. relative humidity 40°C:	50 %
------------------------------	------

---

Min. ambient temperature:	-25 °C
---------------------------	--------

---

Max. ambient temperature:	40 °C
---------------------------	-------

---

24h ambient temperature:	35 °C
--------------------------	-------

---

---

Installation location:	Indoors
------------------------	---------

---

### Material

---

Base unit material:	Polypropylene
---------------------	---------------

---

Cover material:	Polypropylene
-----------------	---------------

---

### Certificates

---

Test mark:	VDE (DIN EN 50085-1 (VDE 0604-1))
------------	-----------------------------------

---