

Main cable junction terminal

HA 25-52



HA 25-52

Main cable junction terminal

Productnumber: 69152201 Dimensions: 157 x 50 x 58 mm

Main cable junction terminal with cross-sectional area $1x25 \text{ mm}^2$ per pole and 2 outlets 16 mm^2 per pole

5-pole - 25/16 mm²



Technical Data

electrical characteristics

| Rated operating voltage AC: | 400 V |
|--|---------------------|
| Number of poles: | 5 |
| Connection 1: Connection type: | Screws |
| Connection 1: Clamping points per pole: | 3 |
| Connection 1: Suitable for Cu conductors: | 1 |
| Connection 1: Connectable conductor cross-section, fine-wire with ferrule (min): | 2.5 mm ² |
| Connection 1: Connectable conductor cross-section, fine-wire with ferrule (max): | 16 mm² |
| Connection 1: Connectable conductor cross-section, single-wire (min): | 1.5 mm² |
| Connection 1: Connectable conductor cross-section, single-wire (max): | 25 mm² |
| Connection 1: Connectable conductor cross-section, stranded (min): | 1.5 mm² |
| Connection 1:Connectable conductor cross- section, stranded (max): | 25 mm² |
| Connection 2: Connection type: | Screws |
| Connection 2: Suitable for Cu conductors: | 1 |
| Connection 2: Connectable conductor cross-section, fine-wire with ferrule (min): | 1.5 mm² |
| Connection 2: Connectable conductor cross-section, fine-wire with ferrule (max): | 10 mm² |
| Connection 2: Connectable conductor cross-section, single-wire (min): | 1.5 mm² |
| Connection 2: Connectable conductor cross-section, single-wire (max): | 16 mm² |
| Connection 2: Connectable conductor cross-section, stranded (min): | 1.5 mm² |
| Connection 2: Connectable conductor cross-section, stranded (max): | 16 mm² |

Dimensions

| Width: | 157 mm |
|---------|--------|
| Length: | 50 mm |
| Height: | 58 mm |

Material characteristics

| Flammability class according with UL94: | V0 |
|--|--------|
| Glow-wire flammability according to EN 60695-2-11: | 960 °C |
| Industry quality: | no |

mechanical properties

| Connection 1: Tightening moment: | 2.5 Nm |
|----------------------------------|--------|
| Connection 2: Tightening torque: | 2.5 Nm |

Material

| Insulating body material: | Thermoplastic |
|---------------------------|---------------|
|---------------------------|---------------|