Main cable junction terminal

HA 35-42



HA 35-42

Main cable junction terminal

Productnumber: 69242201
Dimensions: 157 x 50 x 58 mm

Main line T-piece terminal with connection cross-section 1 x 35 mm² per pole and 2 x 25 mm² outputs per pole

4-pole - 35/25 mm²

Created at 12.10.2024. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Number of poles:	4
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	3
Connection 1: Suitable for Cu conductors:	1
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (min):	2.5 mm²
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (max):	25 mm²
Connection 1: Connectable conductor cross-section, single-wire (min):	2.5 mm²
Connection 1: Connectable conductor cross-section, single-wire (max):	35 mm²
Connection 1: Connectable conductor cross-section, stranded (min):	2.5 mm²
Connection 1:Connectable conductor cross-section, stranded (max):	35 mm²
Connection 2: Connection type:	Screws
Connection 2: Suitable for Cu conductors:	1
Connection 2: Connectable conductor cross-section, fine-wire with ferrule (min):	2.5 mm²
Connection 2: Connectable conductor cross-section, fine-wire with ferrule (max):	16 mm²
Connection 2: Connectable conductor cross-section, single-wire (min):	2.5 mm²
Connection 2: Connectable conductor cross-section, single-wire (max):	25 mm²
Connection 2: Connectable conductor cross-section, stranded (min):	2.5 mm²
Connection 2: Connectable conductor cross-section, stranded (max):	25 mm²

Dimensions

Width:	157 mm
Length:	50 mm
Height:	58 mm

Dimensions

Weight:	0.34 kg

Material characteristics

Flammability class according with UL94:	V0
Glow-wire flammability according to EN 60695-2-11:	960 °C

mechanical properties

Connection 1: Tightening moment:	3.5 Nm
Connection 2: Tightening torque:	3.5 Nm

Sales Information

EAN:	4013902014255
Packing Unit Code:	C62
ETIM Class:	EC000275
Custom tariff number:	85369010

Created at 12.10.2024. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299