Socket outlet combination

# STV 922-K

## STV 922-K

**Socket outlet combination**

CUSTOMIZABLE

Productnumber: 72942201
Dimensions: 200 x 400 x 122 mm

Socket outlet combination, protection class IP44, ready for connection, according to EN 61439-3, high mechanical strength, temperature-resistant, can be combined
Cable insertions:
Top: Pre-embossing 8 x M20, 1 x M25/32
Bottom: Pre-embossing 8 x M20, 1 x M32/25
Left: Pre-embossing 4 x M20/25
Right: Pre-embossing 4 x M20/25
Rear: Pre-embossing 4 x M20/25

**equipped with:**
- **2 x Miniature circuit breaker B16A, 1-pin**
- **1 x Miniature circuit breaker C 16 A, 3p**
- **1 x Miniature circuit breaker C 32 A, 3p**
- **2 x SCHUKO® plug socket (on front), 230V**
- **1 x CEE plug socket outlet (on front) 16A, 400V**
- **1 x CEE plug socket outlet (on front) 32A, 400V**

**Accessories supplied:**
**Attachment bushes: 2x M25, 2x M32, sealing plugs, masking and labelling strips**

IP44 IK08 400V AC

Created at 12.10.2024. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

# Technical Data

## Built-in devices

| | |
|---|---|
| Miniature circuit breaker B16A, 1-pin: | 2 |
| Miniature circuit breaker C 16 A, 3p: | 1 |
| Miniature circuit breaker C 32 A, 3p: | 1 |
| SCHUKO® plug socket (on front), 230V: | 2 |
| CEE plug socket outlet (on front) 16A, 400V: | 1 |
| CEE plug socket outlet (on front) 32A, 400V: | 1 |

## electrical characteristics

| | |
|---|---|
| Rated insulation voltage AC: | 400 V |
| Protection class: | II |
| Type of protection: | IP44 |
| Number of N-potentials: | 1 |
| Number of rows: | 1 |
| Number of modules per row: | 9 |
| with N terminal: | yes |
| with PE terminal: | yes |

## Colours

| | |
|---|---|
| Base unit colour: | grey |
| Cover colour: | grey |

## Dimensions

| | |
|---|---|
| Width: | 200 mm |
| Length: | 400 mm |
| Height: | 122 mm |
| Weight: | 3.31 kg |

## Material characteristics

| | |
|---|---|
| UV-resistant: | yes |

## Material characteristics

| | |
|---|---|
| Halogen free: | yes |
| Flammability class according with UL94: | V2 |
| Glow-wire flammability according to EN 60695-2-11: | 850 °C |

## mechanical properties

| | |
|---|---|
| Type of fastening: | Wall mounting |
| Impact strength: | IK08 |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 25°C: | 95 % |
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -25 °C |
| Max. ambient temperature: | 40 °C |
| 24h ambient temperature: | 35 °C |
| Installation location: | protected outdoor areas |

## Sales Information

| | |
|---|---|
| EAN: | 4013902934669 |
| Packing Unit Code: | C62 |
| ETIM Class: | EC000379 |
| Custom tariff number: | 85369095 |

## Material

| | |
|---|---|
| Base unit material: | Polycarbonate, glass-fibre reinforced |
| Cover material: | Polycarbonate, glass-fibre reinforced |
| Sealing material: | Polyurethane |
| Cover screw material: | Polyamide, glass-fibre reinforced |
| Hinged window material: | Polycarbonate |

Created at 12.10.2024. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

## Cable gland





Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299