

Junction box

## Abox SL-6<sup>2</sup>

This product is outdated. To the successor product:  
<https://www.spelsberg.co.uk/p/80644001>



### Abox SL-6<sup>2</sup>

Junction box

CUSTOMIZABLE

Productnumber: 81081001

Dimensions: 140 x 140 x 79 mm

Junction box, protection class IP54/IP65, nominal cross-section 6 mm<sup>2</sup>, U<sub>i</sub>=690 V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), knockouts, M20/M25/M32, (2 rear, 10 side), internal fixing points, with screwless terminals for standard indoor installations

**grey, with raised, screwless terminal Wago 2006-1201, 5-pole, max. nominal cross-section according to DIN EN 60998: 6 mm<sup>2</sup>, 41 A current load capacity, cross-sections able to be clamped per pole: 4 x 0.5 to 10 mm<sup>2</sup> rigid and flexible**

Accessories supplied:

**4 Attachment bushes IP54 M32 sealing range 13 - 23 mm, 1 sealing plugs M32**



To industrial product:

<https://www.spelsberg.co.uk/p/49081001>

## Technical Data

### electrical characteristics

Rated insulation voltage AC:	690 V
Max. conductor cross section:	6 mm <sup>2</sup>
Protection class:	II
Type of protection:	IP54/IP65
UL Type Rating:	not specified

### Colours

Base unit colour:	grey
Cover colour:	grey

### Dimensions

Width:	140 mm
Length:	140 mm
Height:	79 mm

### Material characteristics

UV-resistant:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	650 °C
Industry quality:	no

### mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK07
Sealable:	yes
Cover screw torque:	1 Nm
Fastening:	internal fixing points

### Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	Indoors

### Material

Base unit material:	Polystyrene
Cover material:	Polystyrene
Cover screw material:	Stainless steel V2A

### Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
------------	---

## Accessories

[20342001 - WST M20 - Twist plug](#)

[20342501 - WST M25 - Twist plug](#)

[20343201 - WST M32 - Twist plug](#)

[21342001 - WNI M20 - Twist nipple](#)

[21342501 - WNI M25 - Twist nipple](#)

[21343201 - WNI M32 - Twist nipple](#)

[22742001 - KVR M20-MGM - Cable gland](#)

[22742101 - KVR M20-GDB/MGM - Cable gland](#)

[22742501 - KVR M25-MGM - Cable gland](#)

[22743201 - KVR M32-MGM - Cable gland](#)

[23142001 - VST M20 - Sealing plugs](#)

[23142501 - VST M25 - Sealing plugs](#)

[23143201 - VST M32 - Sealing plugs](#)

[26012001 - DMS M20/w - Double-membrane seals](#)

[26012501 - DMS M25/w - Double-membrane seals](#)

[26042001 - DMS M20 - Double-membrane seals](#)

[26042501 - DMS M25 - Double-membrane seals](#)

[26043201 - DMS M32 - Double-membrane seals](#)

[26043301 - DMS M32/4 - Double-membrane seals](#)

[26044001 - DMS M40 - Double-membrane seals](#)

[26202001 - BST M20/sw - Ventilation seal](#)

[26242001 - BST M20 - Ventilation seal](#)

## Cable gland

