Junction box

WKE 203 RK

This product is outdated. To the successor product: https://www.spelsberg.co.uk/p/86228301



WKE 203 RK

Junction box

CUSTOMIZABLE

Productnumber: 86220301
Dimensions: 115 x 115 x 93 mm

Junction box, protection class IP66, Ui=450 V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), M25, (3 side), external fixing lugs, with E30 electrical functional integrity according to DIN 4102 Part 12, enclosure and terminal block are made from halogen-free special thermosetting plastic

orange, Junction box 3-pole, clamping capacity per pole 4 x 0.5 - 4 mm²

Accessories supplied:
3 cable glands M25, seal range 6 - 15 mm,
Wall plug set ø 6 mm

IP66 E30 4² 4² IK08 450V AC 450V DC

Technical Data

electrical characteristics

Rated insulation voltage AC:	450 V
Rated insulation voltage DC:	450 V
Min. conductor cross section:	0,5 mm²
max. wire cross section (wire branching):	4 mm²
Min. conductor cross section:	0,5 mm²
Max. conductor cross section:	4 mm²
Protection class:	II
Type of protection:	IP66
secured junction:	no
Circuit integrity class:	E30
Number of poles (T-piece):	3
Number of poles (feed-through):	3
UL Type Rating:	not specified
Number of fuses in T-piece:	0

Colours

Base unit colour:	orange
Cover colour:	orange

Additional features

Range of application:	Connectors and T-pieces

Dimensions

Width:	115 mm
Length:	115 mm
Height:	93 mm
Weight:	1.39 kg

Material characteristics

UV-resistant:	yes

Material characteristics

Halogen free:	yes
Flammability class according with UL94:	V0
Glow-wire flammability according to EN 60695-2-11:	960 °C

mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK08
Sealable:	no
Cover screw torque:	2.5 Nm
Fastening:	external fixing lugs

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902907557
Packing Unit Code:	CT
ETIM Class:	EC002600
Custom tariff number:	85369095

Material

Base unit material:	Duroplast
Cover material:	Duroplast
Sealing material:	Polyurethane
Cover screw material:	Stainless steel V2A

Created at 12.10.2024. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))

Accessories

86040001 - WKE 200 ABL - External attachment set

Cable gland